

FEIN Promotion

FEIN. Unverwüstliche
Elektrowerkzeuge.



Enjoy two-for-one benefits right now:
buy a FEIN KBM 50 / 65 and receive a FEIN ABOP 13-2 SELECT⁺
including a battery starter set worth £560 plus VAT
and the 3-year FEIN PLUS warranty for free.



e.g. KBM 50 U



Between 01.03.-30.6.2017 simply purchase a KBM 50 Q, KBM 50 U, KBM 65 U universal magnetic core drill or a KBM 50 auto automatic magnetic core drill, register the product for the 3-year FEIN PLUS warranty at www.fein.com/warranty within 6 weeks of purchase, enter the promotional code, upload your invoice and then receive a free ABOP 13-2 SELECT⁺ including battery starter set worth £560 plus VAT.

KBM 50/65: lightweight and powerful universal magnetic core drills for universal jobs.

Outstanding quality

- ▶ Extremely tough construction.
- ▶ Outstanding quality of material & workmanship.
- ▶ Swivel-mounted motor cable protection hose.
- ▶ System expertise from one source.

Perfect power to weight ratio

- ▶ FEIN high-power motor.
- ▶ FEIN motor with tacho electronics.
- ▶ Weight-optimised components.
- ▶ Compact, slim machine structure.

Universal use

- ▶ Clockwise / anti-clockwise operation.
- ▶ Electronic speed setting.
- ▶ Extra large stroke range.
- ▶ Variants with MT 3 holder.



Select the right tool for you from the 4 powerful magnetic core drills available.

from **£1159**
plus VAT

Technical data			KBM 50Q	KBM 50U	KBM 65U	KBM 50 auto
Core drilling			▲▲	▲▲	▲▲	▲▲
Twist drilling with drill chuck			▲▲	▲▲	▲▲	▲▲*
Twist drilling with MT mount			-	▲▲	▲▲	▲▲*
Tapping			▲▲	▲▲	▲▲	▲▲*
Countersinking			▲▲	▲▲	▲▲	▲▲*
Reaming			▲▲	▲▲	▲▲	▲▲*
Carbide core drill bit max. diameter	mm		50	50	65	50
HSS core drill bit max. diameter	mm		40	40	45	40
Max. bit drilling depth	mm		50	50 (75) ¹	50 (75) ¹	50 (75) ¹
Twist drilling max. diameter	mm		16	23	25	18 / 23*
Tapping max.	M		16	16	20	16*
Countersinking max. diameter	mm		31	50	50	50*
Reaming max. diameter	mm		16	23	25	23*
Power consumption	W		1200	1200	1300	1200
Power output	W		640	610	730	610
Load speed	1st gear	rpm	130-260	130-260	120-240	130-260
	2nd gear	rpm	260-520	260-520	260-520	260-520
Tool mounting	MT		-	3	3	3
Core drill fitting (tool-free)			3/4" Weldon	3/4" Weldon	3/4" Weldon	3/4" Weldon
Stroke / stroke range	mm		145/315	145/315	145/315	145/315
Magnetic holding force	N		12 500	12 500	14 000	12 500
Magnetic foot dimensions	mm		195 x 90	195 x 90	205 x 95	195 x 90
Cable with plug	m		4	4	4	4
Weight according to EPTA	kg		13.2	13.9	16.1	16.2
Includes			1 magnetic core drill, 1 coolant tank, 1 safety strap, 1 swarf hook, 1 centring pin, 1 contact guard, 1 drift key (KBM 50U, 65U, 50 auto only), 1 case			
Order number	7 270 41 61 00 0	... 40 61 00 0	... 43 61 00 0	... 42 61 00 0
RRP plus VAT			£1159	£1339	£1645	£1695

▲▲ very well suited ¹ optional with accessories * only in manual tool mode

Scope of supply for ABOP 13-2

FREE

ABOP 13-2 SELECT⁺ Battery starter set



Technical data		ABOP 13-2 SELECT ⁺
Battery voltage	V	18
Idling speed	rpm	0-580/0-1760
Load speed	rpm	0-500/0-1500
Torque at max. output power	Nm	24/8
Stall torque	Nm	39/13
Hole diameter, steel / stainless steel	mm	13/10
Hole diameter, light metal	mm	16/10
Hole diameter, wood	mm	37/27
Tapping	M	10
Drill chuck clamping width	mm	1.5-13
Thread on drill shaft		1/2 in-20 UNF
Width across corners	mm	23
Weight according to EPTA (without battery)	kg	1.7
Clockwise/anti-clockwise operation		✓
Acceleration electronics		✓
Includes		1 cordless drill, 1 metal quick-clamping drill chuck, 1 extra handle, 1 plastic tool case
Order number		7 105 03 62 00 0
RRP plus VAT		£336
		Battery starter set
Battery voltage	V	18
Battery capacity	Ah	5
Includes		2 Li-ion batteries, 1 ALG 50 rapid charger, 1 box
Order number		9 26 04 300 03 0
RRP plus VAT		£224

Your specialist dealer will be happy to help: